



WEBBING RETRACTOR 15 MT WITH KOMPAKT PLUS ANTI TORSION CONNECTOR

REF: 117106008033615SF



Description:

Lightweight webbing retractor made of Cutfibre and polyester. The fiber offers maximum resistance and minimum weight is up to 15 times stronger than the steel and up to 40% stronger than the aramid fibers. Designed for vertical use and is ideal for a full-range of applications including construction and general maintenance.

Features:

- Category III EPI
- Includes a strong plastic housing
- Fixation through a carabiner on the top (not included)
- Available with or without energy absorber
- Swivel at the harness connexion side avoids twisting of the webbing
- Contains an energy dissipating element
- Includes a connector with resistance 23 Kn and 19 mm opening
- Connection loop with the connector is protected with heat sealing
- The maximum angle of movement of the user is 40°
- Its use is recommended between -30°C and 50°C
- Extra strong 100% polyethylene tape with a breaking load of more than 2000 Kg
- Includes hanger for an easy transport

Materials: Housing: Hardened plastic; Belt: 100% polyethylene; Carabiner: steel

Available sizes: Available in 6 and 15 meters

Data sheet:

TECHNICAL DATA	
Dimensions (without carabiners)	220x16x70 mm
Max working length	15 m
Belt width	25x2 mm
Breaking force	15 Kn 3 min
Max workload	140 Kg
Total weight	5 Kg approx
Packing unit	1 unit

TECHNICAL DATA ROTARY CARABINER	
Material	Steel
Type	EN 362 Class T
Opening	19 mm
Dimensions	174x22 mm
Resistance	23 Kn
Weight	356 g

