

CLASSIC 3 IN 1 HIGH VISIBILITY JACKET C466

REF: 30104000000C466PW



Description:

Stand out from the crowd with this classic bomber jacket. It features a detachable fur liner, removable sleeves and detachable collar making it adaptable to all weather conditions. Other features include ID pocket, security sleeve pocket and contrast black panels.

Features:

- Waterproof with taped seams preventing water penetration
- Extremely water resistant fabric finish, water beads away from fabric surface
- EN342 Protection against cold certified up to -40°C
- Detachable sleeves, fur liner and fur collar provide multi-way options for the wearer
- · Zipped pockets
- Hook and loop cuffs for a secure fit
- Reflective tape for increased visibility
- Storm flap front to protect against the elements
- Elasticated cuffs for a secure fit
- Certified to EN ISO 20471 after 50x washes
- Two-way zip for quick and easy access
- Phone pocket
- Concealed detachable hood
- 8 pockets for ample storage
- ID card holder for ID card display
- 40+ UPF rated fabric to block 98% of UV rays
- Jacket can be worn three ways for multi use
- Detachable lining for added versatility in all weather conditions
- Side elastic waist for ultimate wearer comfort





CLASSIC 3 IN 1 HIGH VISIBILITY JACKET - C466

REF: 30104000000C466PW

Composition and density:

Shell Fabric: 300D Industry: 100% Polyester, 300D Oxford Weave with a Stain Resistant finish, Double PU Coated 190g Lining Fabric: 100% Polyester 60g Additional Filling Fabric Info: Sleeve: 100% Polyester Filling 120g Removeable Lining: 100% Polyester Fur Lining 400g

Wash care:















Size chart:

Sizes (cm)		XS	S	М	L	XL	XXL	3XL	4XL	5XL
Chest	Α	110	118	126	134	142	150	158	166	174
Hem (relaxed)	В	76	84	92	100	108	116	124	136	144
Sleeve Length	С	81	82	83	84	85	86	87	88	88
Length	D	74	74	76	76	78	78	78	79	79

Available colors and sizes:

- Orange/Black: XS 4XL
- ✓ Yellow/Black: XS 4XL
- ✓ Yellow/Navy: S 3XL







EN ISO 20471 Class 3 RIS 3279 TOM Issue 2 (Orange Only) EN 343 Class 3:1 X WP 15,000mm EN 342 0.344 (M².K/W), 2, X